


**Visual Beacons**
**MS 354 Ø70 Xenon Strobe Beacon**

**SPECIFICATION**

Voltage range (V)	220V AC	24V AC/DC	11-110V DC
Power range(W)	5		
Working Mode	Double Flash		
Materials	Lens PC, Body- ABS		
Protection Rate	IP54		

**ORDER DATA**

Color	Voltage	Order number
Red	220VAC	MS 354.1.220VAC
	24VAC/DC	MS 354.1.24VAC/DC
	11-110VDC	MS 354.1.11-110VDC
Green	220VAC	MS 354.2.220VAC
	24VAC/DC	MS 354.2.24VAC/DC
	11-110VDC	MS 354.2.11-110VDC
Amber	220VAC	MS 354.3.220VAC
	24VAC/DC	MS 354.3.24VAC/DC
	11-110VDC	MS 354.3.11-110VDC
White	220VAC	MS 354.4.220VAC
	24VAC/DC	MS 354.4.24VAC/DC
	11-110VDC	MS 354.4.11-110VDC
Blue	220VAC	MS 354.5.220VAC
	24VAC/DC	MS 354.5.24VAC/DC
	11-110VDC	MS 354.5.11-110VDC

**FEATURES**

- Ø70mm warning light
- Suitable for applications that require downward audible signals in elevated locations
- Reflector with multi-tiered design provides an even and clear illumination throughout the entire lens

**DRAWINGS**
